BAYFIELD®
FREESTANDING WALL SYSTEM

DISTRESSED FACE ADAPTABLE TO MAY DIFFERENT LANDSCAPES

⊘ FEATURES & BENEFITS

- Can be used for straight or curved walls
- Used as seating areas, borders and courtyards
- Can be used for walls up to 3 feet high, including buried course, but excluding the cap
- Columns constructed with the column units can be built up to 6 feet high, including buried course
- Minimum outside radius, measured on the top course to the front of the units: 3 feet, 9 inches*
- Minimum inside radius, measured on the base course to the front of the units: 3 feet, 9 inches*
- Maximum straight-wall length between design elements: 10 feet

*May vary depending on the installation pattern.

▦ SHAPES & SIZES

	Dimensions* H x W x D (in)	Weight* (lbs)	Coverage (sqft)
LARGE WALL UNIT	6 x 18/16 x 9	70	0.71
MEDIUM WALL UNIT	6 x 12/10 x 9	45	0.46
SMALL WALL UNIT	6 x 6/4 x 9	20	0.21
CORNER/ COLUMN	6 x 18 x 9	75	1.13 (linft)
SHORTCUT® CAP	3 x 8/7 x 13	22	0.63 (linft)
STEP	6 x 16 x 12	89	(linft)
TORPEDO™ BASE BLOCK	4 x 15³/₄ x 11	47	1.31 (linft)

For more info visit
AnchorDiamond.com

ANCHOR
DIAMOND®