





DEVELOPED BY  
**ANCHOR**  
DIAMOND  
WALL INDUSTRY EXPERTS



**STRAIGHT**



**BEVELED**



**STONE CUT**




**STONE CUT  
VIRTUAL JOINT**



**QUARRIED**



**SMOOTH**



\* See Installation Guide. Reinforced walls, and other critical walls, must be designed by qualified engineers.

\*\*Dimensions may differ slightly from manufacturer to manufacturer.

†Gravity wall heights are based on project specific conditions and may be lower than this value.

‡Measured on the top course to the front of the wall.

§Measured on the base course to the front of the wall.

‡ varies by face style selection

# DIAMOND PRO®

## RETAINING WALL

A PROVEN BLOCK FOR LARGE  
SCALE PROJECTS IN SERVICE  
SINCE 1999.

### ✓ FEATURES & BENEFITS

- Walls in excess of 50 feet high have been built with the Diamond Pro system when combined with geosynthetic reinforcement.\*
- ASTM C1372 – compliant; ICC evaluated
- Supported by Anchorwall® design software and estimating tools
- Large open cores for ease of handling and drainage aggregate placement during installation.
- Compatible fittings/accessories

<b>H X W X D"</b>	<b>8" X 18" X 12"</b>
<b>WEIGHT</b>	<b>69 – 77 LBS.‡</b>
<b>COVERAGE</b>	<b>1 SQ. FT.</b>
<b>SETBACK; BATTER</b>	<b>1" PER COURSE; 7.1°</b>
<b>MAX. GRAVITY WALL HT.†</b>	<b>4 FT.</b>
<b>MIN. OUTSIDE RADIUS††</b>	<b>2 - 4 FT.‡</b>
<b>MIN. INSIDE RADIUS§</b>	<b>4 - 6 FT.‡</b>



**ANCHOR**  
DIAMOND

**ANCHOR DIAMOND Group**  
5909 Baker Rd. Suite 550  
Minnetonka, MN 55345  
☎ 1-952-933-8855

For more info visit  
[anchordiamond.com](http://anchordiamond.com)



©2023 ANCHOR DIAMOND Group. All rights reserved.  
AD23-001-DIAMOND PRO