



HIGHLAND STONE[®]

RETAINING WALL SYSTEM

VARIED CONTOURS CREATE A STRONG LOOK FOR AN ALTERNATIVE TO NATURAL STONE

☑ FEATURES & BENEFITS









- Can be used to create straight or curved walls
- Gravity wall can be built up to 3 ft. high, including buried cap*
- Original rear-lip locator
- Taller walls can be built using geosynthetic reinforcement when designed by a qualified engineer
- Minimum outside radius, measured on the top course to the front of the units: 4 feet**
- Minimum inside radius, measured on the base course to the front of the units: 8 feet.**
- Setback/System Batter 1 1/8" / 10.6 degree

**The maximum gravity wall height is project specific and may be lower than this height.*

***May vary depending on the installation pattern.*

🧱 SHAPES & SIZES

LARGE WALL UNIT	Dimensions* H x W x D (in)	Weight* (lbs)	Coverage (sqft)
	6 x 18 x 12	78	0.75
MEDIUM WALL UNIT	Dimensions* H x W x D (in)	Weight* (lbs)	Coverage (sqft)
	6 x 12 x 12	59	0.50
SMALL WALL UNIT	Dimensions* H x W x D (in)	Weight* (lbs)	Coverage (sqft)
	6 x 6 x 12	30	0.25
CORNER/COLUMN	Dimensions* H x W x D (in)	Weight* (lbs)	Coverage (sqft)
	6 x 18 x 9	75	1.13
CAP END	Dimensions* H x W x D (in)	Weight* (lbs)	Coverage (sqft)
	3 x 18/12 x 13	44	1.25
STEP	Dimensions* H x W x D (in)	Weight* (lbs)	Coverage (sqft)
	6 x 16/16 x 12	89	