

DIAMOND **PRO**[°] **PS**

RETAINING WALL SYSTEM STONE CUT VIRTUAL JOINT

A RICH FACETED APPEARANCE NOT FOUND IN COMMON COMMERCIAL WALLS

⊘ FEATURES & BENEFITS

- This pinned version of the legendary DIAMOND PRO® block presents the option of 7.1° or Near Vertical 1.7° installation. Additional system batter can be created by alternating pin placement on each course of wall.
- Build walls in excess of 50 feet when combined with geosynthetic reinforcement.[‡]
- ASTM C1372 compliant
- 3 face styles in a single-sized block system
- Large cores for ease of handling and drainage aggregate placement during installation.
- Supported by Anchorwall® design software and estimating tools
- Compatible fittings/accessories
- · Evaluated by the Highway Innovations, Developments, Enhancements, and Advancements (IDEA) program developed by the Federal Highway Administration (FHWA) and administered by the Geo-Institute of the American Society of Civil Engineers (ASCE)



)	8" X 18" X 12"
Γ''	75 LBS.
ε	1 SQ. FT.
R	1" PER COURSE 7/1
	OR NEAR VERTICAL
г.	4 ET

MIN. OUTSIDE RADIUS[†]

1° L 1.7°

4 FT. 6 FT.

4 FT.

MIN. INSIDE RADIUS⁺⁺



* Reinforced walls, and other critical walls, must be designed by qualified engineers. See installation quide.

The maximum gravity wall height is based on project specific conditions and may be lower than this value.

Dimensions and Weights may differ slightly from manufacturer to manufacturer

⁺ Measured on the top course to the front of the wall.

[#] Measured on the base course to the front of the wall.

ANCHOR DIAMOND Group 5909 Baker Rd. Suite 550 Minnetonka, MN 55345 **L** 1-952-933-8855

ANCHOR™ PINS

5" LONG X 0.5" DIAMETER

For more info visit anchordiamond.com



©2023 ANCHOR DIAMOND Group. All rights reserved. AD23-001-DIAMO ND PRO PS STONE CUT VJ