



DIAMOND[®] 10D

RETAINING WALL

DISTRESSED FACE BLOCK WITH A 10" DEPTH LIGHTENS THE BLOCK FOR EASIER INSTALLATION

✔ FEATURES & BENEFITS

- All components are standard split in-line.
- Designed primarily for gravity walls, but also suitable for Anchorplex[®] walls and geosynthetic reinforced walls†
- Supported by Anchorwall[®] design software and estimating tools
- Large open cores for ease of handling and drainage aggregate placement during installation
- Integral locating features establish uniform setback and batter.
- Compatible fittings/accessories

[†]See Installation Guide. Reinforced walls, and other critical walls must be designed by qualified engineers.
^{*}Dimensions and Weights may differ slightly from manufacturer to manufacturer.
^{**}Gravity wall heights are based on project specific conditions and may be lower than this value.
^{††}Measured on the top course to the front of the wall.
^{†††}Measured on the base course to the front of the wall.

H X W X D[*]	6" X 17 ¾" X 10"
WEIGHT[*]	52 LBS.
COVERAGE	0.74 SQ. FT.
SETBACK (PER COURSE); BATTER	1 1/8"; 10.6°
MAX. GRAVITY WALL HT.^{**}	3 FT.
MIN. OUTSIDE RADIUS[†]	3 FT.
MIN. INSIDE RADIUS^{††}	6 FT.