



DIAMOND PRO PS

RETAINING WALL SYSTEM STONE CUT

*A RICH FACETED APPEARANCE
NOT FOUND IN COMMON
COMMERCIAL WALLS*

✓ FEATURES & BENEFITS

- This pinned version of the legendary DIAMOND PRO® block presents the option of 7.1° or Near Vertical 1.7° installation. Additional system batter can be created by alternating pin placement on each course of wall.
- Build walls in excess of 50 feet when combined with geosynthetic reinforcement.†
- ASTM C1372 – compliant
- Large cores for ease of handling and drainage aggregate placement during installation.
- Supported by Anchorwall® design software and estimating tools
- Compatible fittings/accessories
- Evaluated by the Highway Innovations, Developments, Enhancements, and Advancements (IDEA) program developed by the Federal Highway Administration (FHWA) and administered by the Geo-Institute of the American Society of Civil Engineers (ASCE)

ANCHOR™ PINS
5" LONG X 0.5" DIAMETER



† Reinforced walls, and other critical walls, must be designed by qualified engineers. See installation guide.

™ Dimensions and Weights may differ slightly from manufacturer to manufacturer.

* The maximum gravity wall height is based on project specific conditions and may be lower than this value.

† Measured on the top course to the front of the wall.

†† Measured on the base course to the front of the wall.

H X W X D™	8" X 18" X 12"™
WEIGHT™	76 LBS.
COVERAGE	1 SQ. FT.
SETBACK & BATTER	1" PER COURSE 7/1° OR NEAR VERTICAL 1.7°
MAX. GRAVITY WALL HT.*	4 FT.
MIN. OUTSIDE RADIUS†	4 FT.
MIN. INSIDE RADIUS††	6 FT.