



DEVELOPED BY
ANCHOR
DIAMOND
WALL INDUSTRY EXPERTS



DIAMOND PRO®

RETAINING WALL QUARRIED FACE

A NATURAL STONE APPEARANCE
ON A PROVEN BLOCK FOR
LARGE SCALE PROJECTS IN
SERVICE SINCE 1999

✓ FEATURES & BENEFITS

- Walls in excess of 50 feet high have been built with the Diamond Pro system when combined with geosynthetic reinforcement*
- ASTM C1372 – compliant
- ICC evaluated
- Supported by Anchorwall® design software and estimating tools
- Large open cores for ease of handling and drainage aggregate placement during installation
- Anchor Sculpsit•molded face finish
- Compatible fittings/accessories

* See Installation Guide. Reinforced walls, and other critical walls, must be designed by qualified engineers

** Dimensions and Weights may differ slightly from manufacturer to manufacturer

‡ The maximum gravity wall height is project specific and may be lower than this height

† Measured on the top course to the front of the wall

†† Measured on the base course to the front of the wall

| | |
|-------------------------------|----------------------------|
| H X W X D** | 8" X 18" X 12" |
| WEIGHT** | 69 LBS. |
| COVERAGE | 1 SQ. FT. |
| SETBACK & BATTER | 1" PER COURSE; 7.1° |
| MAX. GRAVITY WALL HT.‡ | 4 FT. |
| MIN. OUTSIDE RADIUS† | 4 FT. |
| MIN. INSIDE RADIUS†† | 6 FT. |



ANCHOR
DIAMOND

ANCHOR DIAMOND Group
5909 Baker Rd. Suite 550
Minnetonka, MN 55345
☎ 1-952-933-8855

For more info visit
anchordiamond.com



©2023 ANCHOR DIAMOND Group. All rights reserved.
AD23-001-DIAMOND PRO QUARRIED FACE