



DEVELOPED BY  
**ANCHOR**  
DIAMOND  
WALL INDUSTRY EXPERTS



# DIAMOND PRO<sup>®</sup>

RETAINING WALL  
STONE CUT<sup>®</sup> FACE

A ROUGH-HEWN FACE WITH A  
RICH FACETED APPEARANCE.

## ✓ FEATURES & BENEFITS

- Walls in excess of 50 feet high have been built with the Diamond Pro system when combined with geosynthetic reinforcement.\*
- ASTM C1372 – compliant
- ICC evaluated
- Supported by Anchorwall<sup>®</sup> design software and estimating tools
- Large open cores for ease of handling and drainage aggregate placement during installation.
- Compatible fittings/accessories

\* See Installation Guide. Reinforced walls, and other critical walls, must be designed by qualified engineers.

\*\* Dimensions and Weights may differ slightly from manufacturer to manufacturer.

‡ The maximum gravity wall height is project specific and may be lower than this height.

† Measured on the top course to the front of the wall.

†† Measured on the base course to the front of the wall.

<b>H X W X D**</b>	<b>8" X 18" X 12"</b>
<b>WEIGHT**</b>	<b>77 LBS.</b>
<b>COVERAGE</b>	<b>1 SQ. FT.</b>
<b>SETBACK &amp; BATTER</b>	<b>1" PER COURSE; 7.1°</b>
<b>MAX. GRAVITY WALL HT.‡</b>	<b>4 FT.</b>
<b>MIN. OUTSIDE RADIUS†</b>	<b>4 FT.</b>
<b>MIN. INSIDE RADIUS††</b>	<b>6 FT.</b>



**ANCHOR**  
DIAMOND

**ANCHOR DIAMOND Group**  
5909 Baker Rd. Suite 550  
Minnetonka, MN 55345  
☎ 1-952-933-8855

For more info visit  
[anchordiamond.com](http://anchordiamond.com)



©2023 ANCHOR DIAMOND Group. All rights reserved.  
AD23-001-DIAMOND PRO STONE CUT