



# DIAMOND<sup>®</sup> STONE CUT<sup>®</sup> FACE

## RETAINING WALL

A RICHLY TEXTURED STONE HEWN  
 QUARRIED LOOK

### ✔ FEATURES & BENEFITS

- ASTM C1372 - compliant; ICC evaluated
- Solid top = no core filling
- Designed primarily for gravity walls, but also suitable for Anchorplex<sup>®</sup> walls and geosynthetic reinforced walls†
- Supported by Anchorwall<sup>®</sup> design software and estimating tools
- Integral locating features establish uniform setback and batter.
- Compatible fittings/accessories

<b>H X W X D*</b>	6" X 15 7/8" X 12"
<b>WEIGHT*</b>	69 LBS.
<b>COVERAGE</b>	0.72 SQ. FT.
<b>SETBACK (PER COURSE); BATTER</b>	1 1/8"; 10.6°
<b>MAX. GRAVITY WALL HT.**</b>	4 FT. 6 IN.
<b>MIN. OUTSIDE RADIUS†</b>	2 FT.
<b>MIN. INSIDE RADIUS††</b>	4 FT.

*\*See Installation Guide. Reinforced walls, and other critical walls must be designed by qualified engineers.  
 \*Dimensions and Weights may differ slightly from manufacturer to manufacturer.  
 †Including buried base course, excluding cap course. Assumes proper installation techniques and materials (see Installation Guide), level backfill, no slope at toe of wall, and no surcharge.  
 †Measured on the top course to the front of the wall.  
 ††Measured on the base course to the front of the wall.*