



DEVELOPED BY
ANCHOR
DIAMOND
WALL INDUSTRY EXPERTS



DIAMOND[®] STRAIGHT SPLIT FACE

RETAINING WALL

✓ FEATURES & BENEFITS

- ASTM C1372 - compliant; ICC evaluated
- Solid top = no core filling
- Designed primarily for gravity walls, but also suitable for Anchorplex[®] walls and geosynthetic reinforced walls†
- Supported by Anchorwall[®] design software and estimating tools
- Integral locating features establish uniform setback and batter.
- Compatible fittings/accessories

[†]See Installation Guide. Reinforced walls, and other critical walls must be designed by qualified engineers.
[‡]Dimensions and Weights may differ slightly from manufacturer to manufacturer.
[§]Including buried base course, excluding cap course. Assumes proper installation techniques and materials (see Installation Guide), level backfill, no slope at toe of wall, and no surcharge.
[¶]Measured on the top course to the front of the wall.
^{**}Measured on the base course to the front of the wall.

H X W X D[†]	6" X 17 1/4" X 12"
WEIGHT[‡]	72 LBS.
COVERAGE	0.72 SQ. FT.
SETBACK (PER COURSE); BATTER	1 1/8"; 10.6°
MAX. GRAVITY WALL HT.[§]	4 FT. 6 IN.
MIN. OUTSIDE RADIUS[¶]	4 FT.
MIN. INSIDE RADIUS^{**}	8 FT.



ANCHOR DIAMOND Group
5909 Baker Rd. Suite 550
Minnetonka, MN 55345
☎ 1-952-933-8855

For more info visit
anchordiamond.com

