



DEVELOPED BY  
**ANCHOR**  
DIAMOND  
WALL INDUSTRY EXPERTS



# GEOHOLD<sup>®</sup>

## RETAINING WALL

### STRAIGHT SPLIT FACE

#### ✓ FEATURES & BENEFITS

- ASTM C1372 – compliant
- Designed specifically for geosynthetic-reinforced; can also be used for Anchorplex<sup>®</sup> walls and short gravity walls<sup>†</sup>
- Supported by Anchorwall<sup>®</sup> design software and estimating tools.
- Front channel is provided to accept mechanical grid-connection pipe
- Large thru-cores align vertically from course to course for easy filling
- Top course of wall can be installed upside-down for easy capping
- Standard split face finish
- Complementary fittings/accessories

<sup>\*</sup>See Installation Guide.

<sup>†</sup>Reinforced walls, and other critical walls, must be designed by qualified engineers.

<sup>‡</sup>Dimensions and Weights may differ slightly from manufacturer to manufacturer.

<sup>§</sup>Gravity wall heights are based on project specific conditions and may be lower than this value.

<sup>||</sup>Measured on the top course to the front of the wall.

<sup>¶</sup>Measured on the base course to the front of the wall.

<b>H X W X D<sup>‡</sup></b>	<b>8" X 18" X 11.5"</b>
<b>WEIGHT<sup>§</sup></b>	<b>54 LBS.</b>
<b>COVERAGE</b>	<b>1 SQ. FT.</b>
<b>SETBACK (PER COURSE); BATTER</b>	<b>0.675"; 4°</b>
<b>MAX. GRAVITY WALL HT.<sup>¶</sup></b>	<b>2 FT. 8IN.</b>
<b>MIN. OUTSIDE RADIUS<sup>  </sup></b>	<b>4 FT.</b>
<b>MIN. INSIDE RADIUS<sup>¶¶</sup></b>	<b>6 FT.</b>



**ANCHOR DIAMOND Group**  
5909 Baker Rd. Suite 550  
Minnetonka, MN 55345  
☎ 1-952-933-8855

For more info visit  
[anchordiamond.com](http://anchordiamond.com)



©2023 ANCHOR DIAMOND Group. All rights reserved.  
AD23-001-GEOHOLD