



DEVELOPED BY
ANCHOR
DIAMOND
WALL INDUSTRY EXPERTS



¹See Installation Guide. Reinforced walls, and other critical walls, must be designed by qualified engineers.

²Dimensions and Weights may differ slightly from manufacturer to manufacturer.

³Gravity wall heights are based on project specific conditions and may be lower than this value.

⁴Measured on the top course to the front of the wall.

⁵Measured on the base course to the front of the wall.



VERTICA PRO[®]

RETAINING WALL
BEVELED FACE

USED IN COMMERCIAL SITE
DEVELOPMENT AND ANYWHERE
SPACE IS AT A PREMIUM

✓ FEATURES & BENEFITS

- ASTM C1372 – compliant
- ICC evaluated
- Walls in excess of 60 feet high have been built with the Vertica system when combined with geosynthetic reinforcement[†]
- Supported by Anchorwall[®] design software and estimating tools
- Integral locating features – available in two setback/batter configurations (2° and 4°)
- Compatible fittings / accessories.

H X W X D¹	8" X 18" X 20"
WEIGHT²	112 LBS.
COVERAGE	1 SQ. FT.
SETBACK (PER COURSE); BATTER	9/32"; 2° OR 9/16"; 4°
MAX. GRAVITY WALL HT.³	6 FT.
MIN. OUTSIDE RADIUS⁴	6 FT.
MIN. INSIDE RADIUS⁵	8 FT.



ANCHOR
DIAMOND

ANCHOR DIAMOND Group
5909 Baker Rd. Suite 550
Minnetonka, MN 55345
☎ 1-952-933-8855

For more info visit
anchordiamond.com



©2023 ANCHOR DIAMOND Group. All rights reserved.
AD23-001-VERTICA PRO BEVELED