


Diamond® 10DS RETAINING WALL SYSTEM



The bold look and easy installation of the Diamond® 10DS retaining wall system have long made it the obvious choice for residential and light commercial wall projects. The rough-hewn face lends versatility to this landscaping tradition.


The rear-lip locator provides uniform installation and reduces labor costs. The system is completed with a complementary cap unit.

- Gravity walls can be built up to 3 feet 6 inches high, including buried course, but excluding the cap*
- Taller walls can be built using geosynthetic reinforcement or the Anchorplex[™] retaining wall system when designed by a qualified engineer
- Minimum outside radius, measured on the top course to the front of the units: 2 feet
- Minimum inside radius, measured on the base course to the front of the units: 4 feet

*This height assumes cores are filled with drainage aggregate, level backfill and clean, compacted sand or gravel and no surcharge.



Diamond® 10DS RETAINING WALL SYSTEM



No pins. No mortar. No misalignments. Rear-lip locator, invented by Anchor, makes installation fast and accurate. Anchor – the original rear-lip product!



Visit anchorwall.com for installation instructions.





Units	Stretcher	Сар
Approximate Dimensions*	6" x 171/4" x 10"	Front, 3" x 17½" x 10¾" Back, 3" x 12" x 10¾"
Approximate Weight*	49 lbs.	34 lbs.
Coverage	0.72 sq. ft.	1.22 lin. ft.
Setback/System Batter	1½"/10.6°	

*Product dimensions are height by face length by depth. Actual dimensions and weights may vary from these approximate values due to variations in manufacturing processes. Specifications may change without notice. See your Anchor representative for details, color options, block dimensions and additional information.

© 2011 Anchor Wall Systems, Inc. The Diamond* wall system is manufactured under license from Anchor Wall Systems, Inc. (AWS). The "Anchor A" and "Anchor Build Something Beautiful" logos, "Anchorplex" and "Diamond" are trademarks of AWS. The wall system blocks are covered by the AWS Limited Warranty. For a complete copy, visit your local dealer or see anchorwall.com.

Anchor Wall Systems, Inc., 5959 Baker Road, Suite 390, Minnetonka, MN 55345. A&B0810

72.3051.1 08/11 4015

