



# DIAMOND PRO<sup>®</sup>

RETAINING WALL  
SMOOTH FACE

A MODERN SLEEK FACE ON A PROVEN BLOCK FOR LARGE SCALE PROJECTS IN SERVICE SINCE 1999

## ✔ FEATURES & BENEFITS

- Walls in excess of 50 feet high have been built with the Diamond Pro system when combined with geosynthetic reinforcement\*
- ASTM C1372 – compliant
- ICC evaluated
- Supported by Anchorwall<sup>®</sup> design software and estimating tools
- Large open cores for ease of handling and drainage aggregate placement during installation
- Anchor Sculpsit<sup>•</sup> molded face finish
- Compatible fittings/accessories

\* See Installation Guide. Reinforced walls, and other critical walls, must be designed by qualified engineers  
 \*\*Dimensions and Weights may differ slightly from manufacturer to manufacturer  
 †The maximum gravity wall height is project specific and may be lower than this height  
 ‡Measured on the top course to the front of the wall  
 ††Measured on the base course to the front of the wall

<b>H X W X D**</b>	<b>8" X 18" X 12"</b>
<b>WEIGHT</b>	<b>69 LBS.</b>
<b>COVERAGE</b>	<b>1 SQ. FT.</b>
<b>SETBACK &amp; BATTER</b>	<b>1" PER COURSE; 7.1°</b>
<b>MAX. GRAVITY WALL HT.**</b>	<b>4 FT.</b>
<b>MIN. OUTSIDE RADIUS†</b>	<b>4 FT.</b>
<b>MIN. INSIDE RADIUS††</b>	<b>6 FT.</b>



**ANCHOR DIAMOND Group**  
 5909 Baker Rd. Suite 550  
 Minnetonka, MN 55345  
 ☎ 1-952-933-8855

For more info visit [anchordiamond.com](http://anchordiamond.com)  