


Vertica Pro[®] Retaining Wall System

Estimating Chart for Geosynthetic Reinforcement

No Slopes and No Surcharges

FOR ESTIMATING PURPOSES ONLY - NOT FOR CONSTRUCTION



	CLAY & SILT SOIL	SILTY / CLAYEY SAND SOIL	CLEAN SAND & GRAVEL SOIL
H	$\phi = 26^\circ$ $\gamma = 120 \text{ pcf (19 kN/m}^3\text{)}$	$\phi = 30^\circ$ $\gamma = 120 \text{ pcf (19 kN/m}^3\text{)}$	$\phi = 34^\circ$ $\gamma = 120 \text{ pcf (19 kN/m}^3\text{)}$
4'-0" (1200 mm) 6 Courses	 5.0 FT (1500 mm) 5.0 FT (1500 mm) 5.0 FT (1500 mm)		
6'-0" (1800 mm) 9 Courses	 6.5 FT (1950 mm) 6.5 FT (1950 mm) 6.5 FT (1950 mm) 6.5 FT (1950 mm)	 6.0 FT (1800 mm) 6.0 FT (1800 mm) 6.0 FT (1800 mm)	 5.5 FT (1650 mm) 5.5 FT (1650 mm) 5.5 FT (1650 mm)
8'-0" (2400 mm) 12 Courses	 8.0 FT (2400 mm) 8.0 FT (2400 mm) 8.0 FT (2400 mm) 8.0 FT (2400 mm) 8.0 FT (2400 mm) 8.0 FT (2400 mm)	 7.5 FT (2250 mm) 7.5 FT (2250 mm) 7.5 FT (2250 mm) 7.5 FT (2250 mm)	 7.0 FT (2100 mm) 7.0 FT (2100 mm) 7.0 FT (2100 mm) 7.0 FT (2100 mm)
10'-0" (3000 mm) 15 Courses	 9.5 FT (2850 mm) 9.5 FT (2850 mm) 9.5 FT (2850 mm) 9.5 FT (2850 mm) 9.5 FT (2850 mm) 9.5 FT (2850 mm) 9.5 FT (2850 mm)	 8.5 FT (2550 mm) 8.5 FT (2550 mm) 8.5 FT (2550 mm) 8.5 FT (2550 mm) 8.5 FT (2550 mm)	 8.0 FT (2400 mm) 8.0 FT (2400 mm) 8.0 FT (2400 mm) 8.0 FT (2400 mm) 8.0 FT (2400 mm)
12'-0" (3600 mm) 18 Courses	 Wall design to be performed by a professional engineer	 10.0 FT (3000 mm) 10.0 FT (3000 mm) 10.0 FT (3000 mm) 10.0 FT (3000 mm) 10.0 FT (3000 mm) 10.0 FT (3000 mm)	 9.0 FT (2700 mm) 9.0 FT (2700 mm) 9.0 FT (2700 mm) 9.0 FT (2700 mm) 9.0 FT (2700 mm) 9.0 FT (2700 mm)


©2023 ANCHOR DIAMOND Group. All rights reserved.
AD23-006 01/23
ANCHOR DIAMOND Group
5909 Baker Rd, Suite 550
Minnetonka, MN 55345

Vertica Pro[®] Retaining Wall System

Estimating Chart for Geosynthetic Reinforcement

250 PSF Surcharge

FOR ESTIMATING PURPOSES ONLY - NOT FOR CONSTRUCTION



	CLAY & SILT SOIL	SILTY / CLAYEY SAND SOIL	CLEAN SAND & GRAVEL SOIL
H	$\phi = 26^\circ$ $\gamma = 120 \text{ pcf (19 kN/m}^3\text{)}$	$\phi = 30^\circ$ $\gamma = 120 \text{ pcf (19 kN/m}^3\text{)}$	$\phi = 34^\circ$ $\gamma = 120 \text{ pcf (19 kN/m}^3\text{)}$
4'-0" (1200 mm) 6 Courses			
6'-0" (1800 mm) 9 Courses			
8'-0" (2400 mm) 12 Courses			
10'-0" (3000 mm) 15 Courses			
12'-0" (3600 mm) 18 Courses			


© 2023 ANCHOR DIAMOND Group. All rights reserved.
AD23-006 01/23
ANCHOR DIAMOND Group
5909 Baker Rd, Suite 550
Minnetonka, MN 55345

Vertica Pro[®] Retaining Wall System

Estimating Chart for Geosynthetic Reinforcement

3:1 Crest Slope

FOR ESTIMATING PURPOSES ONLY - NOT FOR CONSTRUCTION



	CLAY & SILT SOIL	SILTY / CLAYEY SAND SOIL	CLEAN SAND & GRAVEL SOIL
H	$\phi = 26^\circ$ $\gamma = 120 \text{ pcf (19 kN/m}^3\text{)}$	$\phi = 30^\circ$ $\gamma = 120 \text{ pcf (19 kN/m}^3\text{)}$	$\phi = 34^\circ$ $\gamma = 120 \text{ pcf (19 kN/m}^3\text{)}$
4'-0" (1200 mm) 6 Courses			
6'-0" (1800 mm) 9 Courses			
8'-0" (2400 mm) 12 Courses			
10'-0" (3000 mm) 15 Courses			
12'-0" (3600 mm) 18 Courses			

©2023 ANCHOR DIAMOND Group. All rights reserved.
AD23-006 01/23

ANCHOR DIAMOND Group
5909 Baker Rd, Suite 550
Minnetonka, MN 55345